Response to OA dated: January 9, 2006

Response dated: April 7, 2006

In the Claims:

All pending claims are represented below. Applicant respectfully reserves the right to

prosecute any originally presented or canceled claims in a continuing or future application.

1. (Original): A system for providing two qualities of service from a single data stream, comprising:

(a) a storage space for storing at least one of a first quality of service choice and a second

quality of service choice for each of a plurality of users;

(b) a processor programmed to direct the data stream for each user according to that user's

quality of service choice;

(c) multicasting apparatus for receiving the data stream from the processor and multicasting

the data stream to each user for which the first quality of service choice is stored in said storage

space; and

(d) a point-to-point device for receiving the data stream from the processor and ensuring that

each user for which the second quality of service is stored in said storage space receives the data

stream.

2. (Original): A system according to claim 1, further comprising a listener adapted to listen for

information sent in the data stream to one of the users of the system.

3. (Original): A system according to claim 1, further comprising a single API for providing

instructions to the processor for both qualities of service.

4. (Original): A system according to claim 1, further comprising a thread of execution for each user

selecting the multicast quality of service, the thread of execution listening on the user's behalf for

a message on the multicast stream then delivering the message to the user.

5. (Previously Presented): A system according to claim 2, further comprising a queue for each

listener, allowing a user to receive messages for both qualities of service.

- 3 -

Response to OA dated: January 9, 2006

Response dated: April 7, 2006

6. (Original): A system according to claim 1, wherein said storage space may store separate

choices for each user for multiple data streams.

(Original): A system according to claim 1, further comprising a filtering device allowing a user

to filter out certain messages in the data stream.

8. (Original): A method for allowing a user to select a quality of service for message delivery,

comprising:

(a) storing at least one of a first quality of service choice and a second quality of service

choice for each user of the system;

(b) processing each message received on a data stream using a single API and redirecting

the message for each user according to that user's quality of service choice;

(c) multicasting the message to each user selecting the first quality of service; and

(d) sending the message directly to each user selecting the second quality of service and

ensuring that the user receives the message.

(Original): A method according to claim 8, further comprising the step of filtering the messages

received by a user by either quality of service

10. (Original): A method according to claim 8, further comprising the step of providing a listener for

each user to listen for messages on the user's behalf.

11. (Original): A method according to claim 8, further comprising the step of queuing messages

sent to a user by either quality of service to be delivered one by one to the user.

12. (Original): A method according to claim 8, further comprising the step of tagging each message

with a sequence number so that a user can tell if a message has been missed.

- 4 -

Response to OA dated: January 9, 2006

Response dated: April 7, 2006

13. (Original): A method according to claim 8, further comprising the step of tagging each message so that a user can tell the data stream from which the message was received.

14. (Original): A method according to claim 9, further comprising the step of allowing a user to select filtering criteria to be used for the filtering.

15. (Original): A method for providing two qualities of service from a single data stream, comprising:

- (a) storing at least one of a first quality of service choice and a second quality of service choice for each of a plurality of users;
- (b) directing each message received on the data stream for each user according to that user's quality of service choice;
 - (c) multicasting the message to each user selecting the first quality of service; and
- (d) sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.
- 16. (Original): A method according to claim 15, further comprising the step of filtering the messages received by a user by either quality of service.
- 17. (Original): A method according to claim 15, further comprising the step of providing a listener for each user to listen for messages on the user's behalf.
- 18. (Original): A method according to claim 15, further comprising the step of queuing messages sent to a user by either quality of service to be delivered one by one to the user.
- 19. (Original): A method according to claim 15, further comprising the step of tagging each message with a sequence number so that a user can tell if a message has been missed.
- 20. (Original): A method according to claim 15, further comprising the step of tagging each

- 5 -

Response to OA dated: January 9, 2006

Response dated: April 7, 2006

message so that a user can tell the data stream from which the message was received.

21. (Original): A computer-readable medium, comprising:

(a) means for storing at least one of a first quality of service choice and a second quality of service choice for each user of a system;

(b) means for processing each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;

(c) means for multicasting the message to each user selecting the first quality of service;

and

(d) means for sending the message directly to each user selecting the second quality of

service and ensuring that the user receives the message.

22. (Original): A computer program product for execution by a server computer for allowing a user

to select a quality of service for message delivery, comprising:

(a) computer code for storing at least one of a first quality of service choice and a second

quality of service choice for each user of a system;

(b) computer code for processing each message received on a data stream using a single

API and redirecting the message for each user according to that user's quality of service choice;

(c) computer code for multicasting the message to each user selecting the first quality of

service: and

(d) computer code for sending the message directly to each user selecting the second

quality of service and ensuring that the user receives the message.

23. (Original): A system for allowing a user to select a quality of service for message delivery,

comprising:

(a) means for storing at least one of a first quality of service choice and a second quality of

service choice for each user of a system;

(b) means for processing each message received on a data stream using a single API and

- 6 -

Response to OA dated: January 9, 2006

Response dated: April 7, 2006

redirecting the message for each user according to that user's quality of service choice;

- (c) means for multicasting the message to each user selecting the first quality of service; and
- (d) means for sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.
- 24. (Original): A computer system comprising: a processor;

object code executed by said processor, said object code configured to:

- (a) store at least one of a first quality of service choice and a second quality of service choice for each user of a system;
- (b) process each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;
 - (c) multicast the message to each user selecting the first quality of service; and
- (d) send the message directly to each user selecting the second quality of service and ensuring that the user receives the message.
- 25. (Previously Presented) The system of claim 1, wherein the point-to-point device ensures that each user receives the data stream by receiving a response from that user, which delivers an acknowledgment of the receipt of data.
- 26. (Previously Presented) The method of claim 8, wherein the step of ensuring that the user receives the message includes receiving a response which delivers an acknowledgment of the receipt of data from that user.
- 27. (Previously Presented) The method of claim 15, wherein the step of ensuring that the user receives the message includes receiving a response which delivers an acknowledgment of the receipt of data from that user.

Response to OA dated: January 9, 2006

Response dated: April 7, 2006

28. (Previously Presented) The computer-readable medium of claim 21, wherein the means for ensuring that the user receives the message includes receiving a response which delivers an acknowledgment of the receipt of data from that user.

29. (Previously Presented) The computer program product of claim 22, further comprising: computer code for receiving a response from each user selecting the second quality of service, which delivers an acknowledgment of the receipt of data.

30. (Previously Presented) The system of claim 23, further comprising:

ensuring that each user selecting the second quality of service receives the message by receiving a response from that user, which delivers an acknowledgement of the receipt of data.